

Solutions for Maximum Performance

Core Products

T-Slot Aluminum Structural Framing

Aluminum Profiles, Fasteners, Accessories


















Table of Contents

Extrusion Profiles - Inch Measurement	6
Extrusion Profiles - Metric Measurement	7
Floor Mounts	8
Corner Brackets	9
Gussets	10
Joining Plates	12
Casters	15
End Fasteners/Connectors	16
Door Hardware, Hinges	17
Panel Materials	19
End Caps	20
T-Nuts	21




IAC is a true Stocking Distributor, offering both Metric and inch profiles, fasteners, and accessories. We manage our own inventory, enabling us to serve our customers efficiently.



IAC's in-house Fabrication Shop utilizes automated cutting, tapping, and drilling equipment. Unlike most distributors who

manually alter extrusion or rely on out-of-town suppliers' facilities, IAC can easily accommodate engineering changes and respond to customer needs quickly. The result is a high-quality product delivered in less time.

IAC is skilled in manufacturing projects to our customer's specific drawings, but we can also provide recommendations to help you determine the best solutions for your needs, including on-site assessments for a true customized approach.







For added flexibility, we offer extruded aluminum in three different forms:

- **Bulk** You may purchase extruded aluminum and accessories directly from our existing inventory
- **Kit Form** All extrusions, fasteners, and accessories are packaged for easy assembly. Extrusions are cut to specifications, and drilled/tapped as needed.
- **Fully Assembled** We assemble your complete project in our shop, to your exact standards. It is shipped to you fully assembled. If necessary, we





1.5" x 1.5" Ultra-Lite Smooth Extrusion

Material: 6063-T6 Finish: Clear Anodized Weight: 1.090 lbs. per foot Slot size: 0.320 inches



1.5" x 1.5" Lite Smooth Extrusion

Material: 6063-T6 Finish: Clear Anodized Weight: 1.114 lbs. per foot Slot size: 0.320 inches



1.5" x 1.5" Regular/Heavy Smooth Extrusion

Material: 6063-T6 Finish: Clear Anodized Weight: 1.300 lbs. per foot Slot size: 0.320 inches



1.5" x 3.0" Lite Smooth Extrusion

Material: 6063-T6 Finish: Clear Anodized Weight: 1.616 lbs. per foot Slot size: 0.320 inches





1.5" x 3.0" Heavy Smooth Extrusion

Material: 6063-T6 Finish: Clear Anodized Weight: 2.397 lbs. per foot Slot size: 0.315 inches



3" x 3" Heavy Smooth Extrusion

Material: 6063-T6 Finish: Clear Anodized Weight: 3.611 lbs. per foot Slot size: 0.315 inches



45mm x 45mm Smooth Extrusion

Material: 6105 T5 Finish: Clear Anodized Weight / m: 1.5 kg/m Weight / ft: 1.05 lbs/ft Slot size: 10 mm



30mm x 30mm Smooth Extrusion

Material: 6105 T5 Finish: Clear Anodized Weight / m: 0.8 Kg/m Weight / ft: .57 lbs/ft Slot size: 8mm





FBM1515CA
Floor Base
Die Cast Aluminum
For use with 1 1/2" x 1 1/2" and
40mm extrusion



FWEB41STQT Floor Base Steel Flanged Black Powder Coath 1 1/2" x 1 1/2" and 40mm extrusion



15FF 5833 Heavy-Duty Floor MountFloor mount w/ base plate.
For use with 3.0" x 3.0" Extrusion (shown). Also available for use with 1.5" x 3.0" Extrusion.



15FF 5830 Floor Mount For use with 1.5" x 3.0" Extrusion Material: Aluminum Finish: Clear Anodized





15CB 4806 6 Hole Inside Corner Bracket

For use with 1.5" x 3.0" and 3.0" x 3.0"Extrusion. For 90 degree connections, no machining required.

Material: Aluminum Finish: Clear Anodized



15CB 4805

8 Hole Inside Corner Bracket

For use with 1.5" x 3.0" and 3.0" x 3.0"Extrusion. For 90 degree connections, no machining required.

Material: Aluminum Finish: Clear Anodized



15CB 4002

4 Hole Slotted Inside Corner Bracket

For use with 1.5" x 3.0" and 3.0" x 3.0" Extrusion. For 90 degree connections, no machining required.

Material: Aluminum Finish: Clear Anodized



15CB 4804

4 Hole Inside Angle Bracket

For use with 1.5" x 3.0" Extrusion. 90 degree connections, no machining required

Material: Aluminum Finish: Clear Anodized





15CB 4803 4 Hole Inside Angle BracketFor use with 1.5" x 3.0" and 3.0" x 3.0" Extrusion. 90 degree connections, no machining required.

Material: Aluminum Finish: Clear Anodized



15CB 4843 8 Hole Inside Gusset Corner BracketFor use with 1.5" x 3.0" or 3.0" x 3.0"
Extrusion. For 90 degree connections, no machining required.
Material: Aluminum



G1515
2 Hole Slotted Gusset - Inch
For use with 1.5" x 1.5" Extrusion.
For 90 degree connections, no machining required. Alignment Tabs for easy, accurate connections.
Material: Die Cast Aluminum



G4545
2 Hole Slotted Gusset - Metric
For use with 45mm x 45mm
Extrusion. For 90 degree
connections, no machining required.
Alignment Tabs for easy, accurate





G4590
4 Hole Slotted Gusset - Metric
For use with 45mm x 45mm
Extrusion. For 90 degree
connections, no machining required.
Alignment Tabs for easy, accurate
connections.

Material: Die Cast Aluminum



EB 17

Double Steel Corner Bracket

For use with Extrusion with slot sizes 5/16" and 1/4"

Material: Steel



15CB4801 2 Hole Inside Corner BracketFor use with 1.5" x 1.5" profiles
Material: anodized aluminum
Finish: clear anodized

Finish: Zinc Plating



15CB4842 4 Hole Inside Gusset Corner Bracket For use with 1.5" x 1.5" profiles Material: anodized aluminum Finish: clear anodized





15JP 45012 Hole Joining PlateMaterial: anodized aluminumFinish: clear anodized



15JP 4502
3 Hole Joining Plate
Material: anodized aluminum
Finish: clear anodized



15JP 4506 5 Hole Tee Joining Plate For use with 1.5" x 1.5" profiles Material: anodized aluminum Finish: clear anodized



15 JP 4505 4 Hole 90° Joining Plate Material: anodized aluminum Finish: clear anodized





15JP 4507
5 Hole 90° Joining Plate
Material: anodized aluminum
Finish: clear anodized



5TJP 15155 Hole T Joining PlateMaterial: anodized aluminumFinish: clear anodized



5LJP 1515
5 Hole L 90° Joining Plate
Material: anodized aluminum
Finish: clear anodized



15MC 099D084
Milling T-Slot Connector
No machining required.
Clean, Flush look
Use with 8mm or 5/16" slot profiles





15JP 4504 4 Hole Joining Plate Dimensions 3" x 3"jo For use joining 1.5" x 1.5" profiles with 1.5" x 3.0" profiles Material: anodized aluminum Finish: clear anodized



15JP 4509
8 Hole Joining Plate
Dimension 6.0" x 3.0"
For use joining 1.5" x 3.0" profiles
Material: anodized aluminum
Finish: clear anodized





No-Mar Caster without Brake 3 1/2" Diameter 1/2—13 Stem
For use with 1 1/2" x 1 1/2" extrusion



No-Mar Caster with Brake 3 1/2' Diameter 1/2-13 Stem For use with 1 1/2" x 1 1/2" extrusion



CM06047-1515
IAC Custom Caster Plate
Tapped 1/2—13
For use with 1 1/2" x 1 1/2" extrusion



LF-1515
Leveling Feet
Accommodates uneven floors or slight inclines
5/16—18 Stem
1 1/2" No Skid Pad
For use with 1 1/2" x 1 1/2" extrusion
Other Sizes & Styles Available





EB 36 45° Angle Block Create a 45° degree angle, no machining required.



ACK1515
Adjustable Angle Connector
Joint Composition-Die-cast Zinc
Fasteners-Steel
1.5" x 1.5"



15EFC End FastenerKeeps profile aligned, prevents rotation. For use with 8mm and 5/16" slots.



EFH29A
Half End Fastener
Keeps profile aligned, prevents
rotation. Eliminates the need to trim
panel material when inserted in the
slot. For use with 8mm and 5/16"
slots.





Fixed Hinge Nylon-Fiberglass reinforced. For use with profiles: 1.5" x 1.5" 45mm x 45mm



BC093045
Ball Catch
May be used for swinging or sliding

doors. Use with all profile sizes. Material: Fiberglass reinforced nylon

Ball screw: M8 x 12



SL0957101 Slam Latch

Fits most profiles. Solid, secure with 2 keys.

Material: Die cast zinc



EB130 Lift-off Hinge

Right or Left-hand hinges available.

For use with 5/16" slots Material: Aluminum Finish: Clear Anodized





092002 Strap Handle

Material: Nylon-Fiberglass

reinforced Color: Black



EF22HD Heavy-Duty Magnetic Door Latch Assembly

Material: Steel

Finish: Zinc Plate and Black Powder

Coat



F93082 Dead Bolt Latch

Material: Mounting Plates: Clear

Anodized Aluminum

Dead Bolt: Zinc Plated Steel

Hardware Included



15HI8514

Aluminum Butt Hinge

Material: Aluminum Hinge, Steel Pin

75 lb. Capacity per Hinge





Polycarbonate Panel Material 3/16" thickness Clear, Smoke, Bronze

Other colors available 4' x 8' sheets or custom cut



PVC Coated Wire Mesh

1" x 1" 12 gauge Yellow or Black 1/2" x 1/2" 16 gauge Yellow or Black



PVC Foam Board Panel Material

1/4" thickness Black, Blue, Red, Green, Beige, Grey Additional colors upon request




EB63 15AC7105 Mesh Retainer

1.5" Mesh Retainer for use with Wire Mesh Panel material, when Wire Mesh is inserted in the Extrusion Slot.

Material: Aluminum Finish: Clear Anodized





End Caps Nylon-Fiberglass Reinforced

Extrusion Size	Part Number
1.5" x 1.5"	EC1515
1.5" x 3.0"	EC1530
3.0" x 3.0"	EC3X3
30mm x 30mm	EC3030
45mm x 45mm	EC4545



T-Nuts (Spring Bearing)

Slot Size	Metric Size	Part Number
5/16" and 8MM	1/4 - 20	DSN - 1/4 - 20
	10 - 32	DSN - 10 - 32
	5/16 - 18	DSN - 5/16 - 18

T-Nuts (No Bearing)

Slot Size	Metric Size	Part Number
5/16" and 8MM	1/4 - 20	DN - 1/4 - 20
	10 - 32	DN - 10 - 32
	5/16 - 18	DN - 5/16 - 18



Hammer Nuts

Slot Size	Metric Size	Part Number
5/16" and 8MM	M4	HN8-M4
	M5	HN8-M5
	M6	HN8-M6
	1/4 - 20	HN8-20
	10-32	HN8-32
10mm	M4	HN10-M4
	M5	HN10-M5
	M6	HN10-M6
	M8	HN10-M8
	1/4 - 20	HN10-20
	10-32	HN10-32
	5/16 - 18	HN10-18









All of the products shown in this catalog are stocked in our warehouse. Other profile sizes and accessories are available. Please call us at 800-644-6215 for more information.



Solutions for Maximum Performance

5719 Webster St. • Dayton, Ohio 45414

Phone: 937.890.6215 · Fax: 937.890.6217

Toll Free: 800. 644.6215

Email: sales@iacohio.com · www.iacohio.com





